

Product Specifications

Plinth

KEY FEATURES

- Plinth allows functional storage of excess cable assemblies for Signamax Steel and Aluminum Cabinets
- Provides additional spacing to maximize airflow when using an air dam or containment solution



STANDARD ORDERING

PART NO.	DESCRIPTION
DCPL-66S-CC	Steel Plinth, 3.5" H x 23.6" D x 23.6" W
DCPL-68S-CC	Steel Plinth, 3.5" H x 23.6" D x 31.5" W
DCPL-610S-CC	Steel Plinth, 3.5" H x 23.6" D x 39.4" W
DCPL-611S-CC	Steel Plinth, 3.5" H x 23.6" D x 43.3" W
DCPL-612S-CC	Steel Plinth, 3.5" H x 23.6" D x 47.2" W
DCPL-88S-CC	Steel Plinth, 3.5" H x 31.5" D x 31.5" W
DCPL-810S-CC	Steel Plinth, 3.5" H x 31.5" D x 39.4" W
DCPL-811S-CC	Steel Plinth, 3.5" H x 31.5" D x 43.3" W
DCPL-812S-CC	Steel Plinth, 3.5" H x 31.5" D x 47.2" W

Specify color by substituting **CC** in P/N for the following: LG BK

SPECIFICATIONS

DIMENSIONS

DCPL-66S: 3.5" H x 23.6" D x 23.6" W (89mm x 600mm x 600mm)
DCPL-68S: 3.5" H x 23.6" D x 31.5" W (89mm x 600mm x 800mm)
DCPL-610S: 3.5" H x 23.6" D x 39.4" W (89mm x 600mm x 1000mm)
DCPL-611S: 3.5" H x 23.6" D x 43.3" W (89mm x 600mm x 1100mm)
DCPL-612S: 3.5" H x 23.6" D x 47.2" W (89mm x 600mm x 1200mm)
DCPL-88S: 3.5" H x 31.5" D x 31.5" W (89mm x 800mm x 800mm)
DCPL-810S: 3.5" H x 31.5" D x 39.4" W (89mm x 800mm x 1000mm)
DCPL-811S: 3.5" H x 31.5" D x 43.3" W (89mm x 800mm x 1100mm)
DCPL-812S: 3.5" H x 31.5" D x 47.2" W (89mm x 800mm x 1200mm)

CONSTRUCTION

Frame: 2 mm steel
Finish: Electrostatic powder paint
Adapter Housing: Carbon Steel
Mounting Screws: Carbon Steel

WEIGHT

DCPL-66S: 13.1lb (5.95kg)
DCPL-68S: 15.7lb (7.12kg)
DCPL-610S: 17.5lb (7.94kg)
DCPL-611S: 19.5lb (8.84kg)
DCPL-612S: 21.5lb (9.75kg)
DCPL-88S: 16lb (7.26kg)
DCPL-810S: 17.9lb (8.12kg)
DCPL-811S: 19.8lb (8.98kg)
DCPL-812S: 21.8lb (9.89kg)

ENVIRONMENTAL CONDITIONS

Service Temperature: -40 °F to 176 °F (-40 °C to 80 °C)
Operating RH: 93% Max (non-condensing)

WARRANTY

5 - Year Limited