SIGNAMAX DATA CENTER SOLUTIONS

Product Specifications

Vertical Chassis Rail & Clamps Management System

KEY FEATURES

- Vertical Channel and Chassis Rails for Steel and Aluminium Cabinets
- Provides additional rail options for multiple applications with Signamax Cabinets
- Vertical cable channel provides scalable cable clamp positions



Vertical Chassis Rail, Fixed Fingers

Vertical Chassis Rail

Vertical Channel

Cable Clamp

STANDARD ORDERING

PART NO.	DESCRIPTION
VERTICAL RAIL AND CHANNEL	
DCPR-0600	Veritcal Chassis Rail, Fixed Fingers for 24" Cabinets
DCPR-0800	Veritcal Chassis Rail, Fixed Fingers for 32" Cabinets
DCPR-1000	Veritcal Chassis Rail, Fixed Fingers for 40" Cabinets
DCPR-1200	Veritcal Chassis Rail, Fixed Fingers for 48" Cabinets
DCCR-0600	Veritcal Chassis Rail for 24" Cabinets
DCCR-0800	Veritcal Chassis Rail for 32" Cabinets
DCCR-1000	Veritcal Chassis Rail for 40" Cabinets
DCVR-0600	24 in. Vertical Channel, Aluminum
DCVR-0800	32 in. Vertical Channel, Aluminum
DCVR-1000	40 in. Vertical Channel, Aluminum
DCVR-1200	48 in. Vertical Channel, Aluminum
CABLE CLAMPS	
DCCR-0812CP	Cable Clamp for Vertical Channel, 0.33"-0.47"
DCCR-1118CP	Cable Clamp for Vertical Channel, 0.43"-0.71"
DCCR-1223CP	Cable Clamp for Vertical Channel, 0.47"-0.9"

SPECIFICATIONS

CONSTRUCTION

Vertical Rail
- **Material:** 1.5 mm Steel
- **Finish:** Zinc Plated

Vertical Channel
- **Material:** Anodized Aluminum Profile
- **Finish:**Anodization

Cable Clamp
- **Material:** Carbon Steel
- **Finish:** Zinc Plated

DIMENSIONS

DCPR-0600: .6" W x 2.5" H x 13.3" L (15 x 64 x 339 mm)
DCPR-0800: .6" W x 2.5" H x 21.2" L (15 x 64 x 539 mm)
DCPR-1000: .6" W x 2.5" H x 29.1" L (15 x 64 x 739 mm)
DCPR-1200: .6" W x 2.5" H x 37" L (15 x 64 x 939 mm)
DCCR-0600: 1.9" W x 1.7" H x 13.2" L (49.5 x 43.5 x 336 mm)
DCCR-0800: 1.9" W x 1.7" H x 21.1" L (49.5 x 43.5 x 536 mm)
DCCR-1000: 1.9" W x 1.7" H x 29" L (49.5 x 43.5 x 736 mm)
DCVR-0600: 1.3" W x 0.8" H x 24" L (34 x 20 x 600 mm)
DCVR-0800: 1.3" W x 0.8" H x 32" L (34 x 20 x 800 mm)
DCVR-1000: 1.3" W x 0.8" H x 40" L (34 x 20 x 1000 mm)
DCVR-1200: 1.3" W x 0.8" H x 48" L (34 x 20 x 1200 mm)
DCCR-0812CP Cable Diameter: 0.33" - 0.47" (8 - 12 mm)
DCCR-1118CP Cable Diameter: 0.43" - 0.71" (11 - 18 mm)
DCCR-1223CP Cable Diameter: 0.47" - 0.9" (12 - 23 mm)

WEIGHT

DCPR-0600: 0.8 lb. (0.36 kg)
DCPR-0800: 1 lb. (0.48 kg)
DCPR-1000: 1.3 lb. (0.6 kg)
DCPR-1200: 1.6 lb. (0.72 kg)
DCCR-0600: 1 lb. (0.47 kg)
DCCR-0800: 1.4 lb. (0.63 kg)
DCCR-1000: 1.8 lb. (0.79 kg)
DCVR-0600: 0.6 lb. (0.30 kg)
DCVR-0800: 0.86 lb. (0.39 kg)
DCVR-1000: 1.1 lb. (0.49 kg)
DCVR-1200: 1.3 lb. (0.59 kg)
DCCR-0812CP Cable Diameter: 0.09 lb. (0.042 kg)
DCCR-1118CP Cable Diameter: 0.10 lb. (0.048 kg)
DCCR-1223CP Cable Diameter: 0.12 lb. (0.054 kg)

ENVIRONMENTAL CONDITIONS

Service Temperature: 14 to 140 °F (-10 to 60 °C)
Operating RH: 93% Max (non-condensing)

WARRANTY

5 - Year Limited

www.signamax.com
999 N.W. 159th Drive
Miami, FL 33169
Tel: 800.446.2377

COPYRIGHT 2007 SIGNAMAX, INC. ■ ALL RIGHTS RESERVED ■ SPECIFICATIONS SUBJECT TO CHANGE

CONNECT WITH US