

## SFP MODULES



COMMERCIAL						
PART NUMBER	DESCRIPTION	TEMP RANGE	FIBER CONNECTOR	FIBER TYPE	DISTANCE	
<b>10G</b>						
065-80SR10G300M	10GBase-SR 850nm	32 to 158 °F	LC	Multimode	300 m	
065-80LR10G10KM	10GBase-LR 1310nm	32 to 158 °F	LC	Singlemode	10 km	
<b>GIGABIT DUAL FIBER</b>						
065-79SXMG	1000SX 850nm	32 to 158 °F	LC	Multimode	220/550 m	
065-79SXEDMG	1000SX 1310nm	32 to 158 °F	LC	Multimode	2 km	
065-79LXMG	1000LX 1310nm	32 to 158 °F	LC	Singlemode	10 km	
065-79LXEDMG	1000LX 1310nm	32 to 158 °F	LC	Singlemode	40 km	
065-79XDMG	1000ZX 1550nm	32 to 158 °F	LC	Singlemode	40 km	
065-79ZXMG	1000ZX 1550nm	32 to 158 °F	LC	Singlemode	80 km	
065-79EZXMG	1000EZ 1550nm	32 to 158 °F	LC	Singlemode	110 km	
<b>GIGABIT WDM SINGLE FIBER</b>						
065-79LX1WDMA1550	WDM 1.25G Tx:1310nm/Rx: 1550nm	32 to 158 °F	LC	Singlemode	10 km	
065-79LX1WDMB1550	WDM 1.25G Tx:1550nm/Rx: 1310nm	32 to 158 °F	LC	Singlemode	10 km	
065-79LX2WDMA1550	WDM 1.25G Tx:1310nm/Rx: 1550nm	32 to 158 °F	LC	Singlemode	20 km	
065-79LX2WDMB1550	WDM 1.25G Tx:1550nm/Rx: 1310nm	32 to 158 °F	LC	Singlemode	20 km	
<b>GIGABIT CWDM SINGLE FIBER</b>						
065-79LXCWDMA1490	CWDM 1.25G Tx:1310m/Rx:1490nm	32 to 158 °F	LC	Singlemode	10 km	
065-79LXCWDMB1490	CWDM 1.25G Tx:1490m/Rx:1310nm	32 to 158 °F	LC	Singlemode	10 km	
<b>100FX DUAL FIBER</b>						
065-73FXMM5MG	100FX / OC-3 / STM-1	32 to 158 °F	LC	Multimode	5 km	
065-73FXSM20MG	100FX / OC-3 / STM-1	32 to 158 °F	LC	Singlemode	20 km	
065-73FXSM40MG	100FX / OC-3 / STM-1	32 to 158 °F	LC	Singlemode	40 km	
065-73FXSM80MG	100FX / OC-3 / STM-1	32 to 158 °F	LC	Singlemode	80 km	
<b>100FX WDM SINGLE FIBER</b>						
065-73-MWA15	WDM 155Mb Tx:1310nm/Rx:1550nm	32 to 158 °F	LC	Multimode	2 km	
065-73-MWB15	WDM 155Mb Tx:1550nm/Rx:1310nm	32 to 158 °F	LC	Multimode	2 km	

FOR ADDITIONAL INFORMATION VISIT [WWW.SIGNAMAX.COM](http://WWW.SIGNAMAX.COM) OR CALL CUSTOMER SERVICE (800) 446-2377 / (305) 944-7710

CONNECT WITH US



## SFP MODULES



### COMMERCIAL

PART NUMBER	DESCRIPTION	TEMP RANGE	CONNECTOR	FIBER TYPE	DISTANCE
<b>COPPER</b>					
065-791000TTXMG	10/100/1000TX	32 to 158 °F	RJ-45	Twisted Pair	100 m
065-73TXMG	10/100TX	32 to 158 °F	RJ-45	Twisted Pair	100 m
<b>10G DIRECT ATTACH CABLE</b>					
065-80PDAC1M	Passive 10G Base-CU	32 to 158 °F	N/A	Twinax	1 m
065-80PDAC3M	Passive 10G Base-CU	32 to 158 °F	N/A	Twinax	3 m
065-80PDAC5M	Passive 10G Base-CU	32 to 158 °F	N/A	Twinax	5 m
065-80PDAC7M	Passive 10G Base-CU	32 to 158 °F	N/A	Twinax	7 m
065-80ADAC7M	Active 10G Base-CU	32 to 158 °F	N/A	Twinax	7 m
065-80ADAC10M	Active 10G Base-CU	32 to 158 °F	N/A	Twinax	10 m

### INDUSTRIAL

PART NUMBER	DESCRIPTION	TEMP RANGE	FIBER CONNECTOR	FIBER TYPE	DISTANCE
<b>GIGABIT DUAL FIBER</b>					
065-79SXMG-H	1000SX 850nm	-40 to 185 °F	LC	Multimode	220/550 m
065-79SXEDMG-H	1000SX 1310nm	-40 to 185 °F	LC	Multimode	2 km
065-79LXMG-H	1000LX 1310nm	-40 to 185 °F	LC	Singlemode	10 km
065-79LXEDMG-H	1000LX 1310nm	-40 to 185 °F	LC	Singlemode	40 km
065-79XDMG-H	1000ZX 1550nm	-40 to 185 °F	LC	Singlemode	40 km
065-79ZXMG-H	1000ZX 1550nm	-40 to 185 °F	LC	Singlemode	80 km
065-79EZXMG-H	1000EZ 1550nm	-40 to 185 °F	LC	Singlemode	110 km
<b>100FX DUAL FIBER</b>					
065-73FXMM5MG-H	100FX / OC-3 / STM-1	-40 to 185 °F	LC	Multimode	5 km
065-73FXSM20MG-H	100FX / OC-3 / STM-1	-40 to 185 °F	LC	Singlemode	20 km

FOR ADDITIONAL INFORMATION VISIT [WWW.SIGNAMAX.COM](http://WWW.SIGNAMAX.COM) OR CALL CUSTOMER SERVICE (800) 446-2377 / (305) 944-7710