

Product Specifications

Panel-Mount Cable Management Bars



KEY FEATURES

- Designed for rear cable management on rack-mounted patch panels.
- Enhanced slide in bracket for easy installation during or after initial set up without the need for mounting screws.
- Constructed with notches for air flow circulation & cable ties for additional strain relief.
- Compatible with most Signamax Patch Panels for both copper and fiber solutions

The Signamax Panel-Mount Cable Management Bars provide a simple means of organizing and managing patch and trunk cables on the rear of an equipment rack. These cable management bars are available in either nickel plated steel or thermoplastic with steel brackets. Both styles are for one unit rack space (1.75" H) and offer simple installation into Signamax patch panels integrated for the bars.

ORDERING INFORMATION

PART NO.	DESCRIPTION
CMB-250	Panel-Mount Cable Management Bar, Plastic Body
CMB-550	Panel-Mount Cable Management Bar, Metal Body

Cable Management Bars are not compatible with the following Signamax Patch Panels:
All Angled panels, Modular-Telco panels, Standard Density panels, DE-Series panels

SPECIFICATIONS

MOUNTING DIMENSIONS:

Depth:

CMB-250-P: 2.50" (63.5 mm)

CMB-550-M: 5.50" (140 mm)

Width: 17.25" (438 mm)

CONSTRUCTION

CMB-250-P: Thermoplastic with steel brackets

CMB-550-M: Nickel-plated steel

ENVIRONMENTAL CONDITIONS

Operating Temperature: 14°F to 140 °F (-10 °C to 60 °C)

Storage Temperature: -40 °F to 158 °F (-40 °C to 70 °C)

Operating RH: 93% Max (non-condensing)

WARRANTY

5 - Year Limited Component

